





Dacheng mechanical equipment manufact...



65 mm x 100 mm x 18 mm SKF 7013 ACD/P4AL angular contact ball bearings

Bearing No. 7013 ACD/P4AL

7013 ACD/P4AL Bearing 2D drawings and 3D CAD models

Size	100x65x18 mm
Bore Diameter	100 mm
Outer Diameter	65 mm
Width	18 mm
d	65 mm
D	100 mm
B	18 mm
d ₁	75.8 mm
d ₂	75.8 mm
D ₁	89.2 mm
b	1.9 mm
C ₁	9.7 mm
C ₂	4.3 mm
C ₃	3.8 mm
r _{1,2} - min.	1.1 mm
r _{3,4} - min.	0.6 mm
a	28.3 mm
d _a - min.	71 mm
d _b - min.	71 mm
D _a - max.	94 mm
D _b - max.	96.8 mm
r _a - max.	1 mm
r _b - max.	0.6 mm
d _n	78.1 mm



Dacheng mechanical equipment manufact...

Basic dynamic load rating - C	39 kN
Basic static load rating - C_0	35.5 kN
Fatigue load limit - P_u	1.5 kN
Limiting speed for grease lubrication	12000 r/min
Limiting speed for oil lubrication	19000 mm/min
Ball - D_w	11.112 mm
Ball - z	20
G_{ref}	5.7 cm ³
Calculation factor - e	0.68
Calculation factor - Y_2	0.87
Calculation factor - Y_0	0.38
Calculation factor - X_2	0.41
Calculation factor - Y_1	0.92
Calculation factor - Y_2	1.41
Calculation factor - Y_0	0.76
Calculation factor - X_2	0.67
Preload class A - G_A	240 N
Preload class B - G_B	480 N
Preload class C - G_C	960 N
Preload class D - G_D	1920 N
Calculation factor - f	1.13
Calculation factor - f_1	0.99
Calculation factor - f_{2A}	1
Calculation factor - f_{2B}	1.02
Calculation factor - f_{2C}	1.05
Calculation factor - f_{2D}	1.08
Calculation factor - f_{HC}	1



Dacheng mechanical equipment manufact...

Preload class A	174 N/micron
Preload class B	227 N/micron
Preload class C	302 N/micron
Preload class D	409 N/micron
d_1	75.8 mm
d_2	75.8 mm
D_1	89.2 mm
C_1	9.7 mm
C_2	4.3 mm
C_3	3.8 mm
$r_{1,2}$ min.	1.1 mm
$r_{3,4}$ min.	0.6 mm
d_a min.	71 mm
d_b min.	71 mm
D_a max.	94 mm
D_b max.	96.8 mm
r_a max.	1 mm
r_b max.	0.6 mm
d_n	78.1 mm
Basic dynamic load rating C	39 kN
Basic static load rating C_0	35.5 kN
Fatigue load limit P_u	1.5 kN
Attainable speed for grease lubrication	12000 r/min
Attainable speed for oil-air lubrication	19000 r/min
Ball diameter D_w	11.112 mm
Number of balls z	20
Reference grease quantity G_{ref}	5.7 cm ³
Preload class A G_A	240 N
Static axial stiffness, preload class A	174 N/ μ m



Dacheng mechanical equipment manufact...

Preload class B G_B	480 N
Static axial stiffness, preload class B	227 N/ μ m
Preload class C G_C	960 N
Static axial stiffness, preload class C	302 N/ μ m
Preload class D G_D	1920 N
Static axial stiffness, preload class D	409 N/ μ m
Calculation factor f	1.13
Calculation factor f_1	0.99
Calculation factor f_{2A}	1
Calculation factor f_{2B}	1.02
Calculation factor f_{2C}	1.05
Calculation factor f_{2D}	1.08
Calculation factor f_{HC}	1
Calculation factor e	0.68
Calculation factor (single, tandem) Y_2	0.87
Calculation factor (single, tandem) Y_0	0.38
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back-to-back, face-to-face) Y_1	0.92
Calculation factor (back-to-back, face-to-face) Y_2	1.41
Calculation factor (back-to-back, face-to-face) Y_0	0.76
Calculation factor (back-to-back, face-to-face) X_2	0.67
Mass bearing	0.43 kg