



Dacheng mechanical equipment manufact...



63208LLU Bearing 2D drawings and 3D CAD models

40,000 mm x 80,000 mm x 30,200 mm NTN
63208LLU deep groove ball bearings

Bearing No. 63208LLU

Size	40x80x30.200 mm
Bore Diameter	40,000 mm
Outer Diameter	80,000 mm
Width	30,200 mm
d	40,000 mm
D	80,000 mm
B	30,200 mm
C	30,200 mm
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.604
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	40MM Bore; 80MM



Dacheng mechanical equipment manufact...

	Outside Diameter; 30.18MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cag
Other Features	Deep Groove Cartridge Type Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Item Number	63208LLU
Weight / LBS	1.332
Outer Race Width	1.188 Inch 30.18 Millimeter
Bore	1.575 Inch 40 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	3.15 Inch 80 Millimeter
bore diameter:	40 mm
static load capacity:	2390 N
outside diameter:	80 mm
precision rating:	ISO Class 0
overall width:	30.2 mm
finish/coating:	Uncoated
bore type:	Round
bearing material:	High Carbon Chrome Steel
closure type:	Double Sealed
cage material:	Steel



Dacheng mechanical equipment manufact...

row type & fill slot:	Single Row Non-Fill Slot
inner ring width:	30.20 mm
snap ring included:	Without Snap Ring
outer ring width:	30.20 mm
internal clearance:	CN
maximum rpm (grease):	5600 rpm
operating temperature range:	-40 to 120 ° C
fillet radius:	1.1 mm
dynamic load capacity:	5100 N
manufacturer product page:	Click here